

IDAHO DEPARTMENT OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

Office Use Only  
Inspected by \_\_\_\_\_  
Twp \_\_\_\_\_ Rge \_\_\_\_\_ Sec \_\_\_\_\_  
\_\_\_\_\_ 1/4 \_\_\_\_\_ 1/4 \_\_\_\_\_ 1/4  
Lat: \_\_\_\_\_ Long: \_\_\_\_\_  
 Air  Flowing Artesian

1. WELL TAG NO. D 13918 MAR 16 2001  
DRILLING PERMIT NO. \_\_\_\_\_  
Other IDWR No. 768028 IDWR North

2. OWNER:  
Name John Burgoy  
Address Timber Haven Rd P.O. Box 811  
City Sagle State Id. Zip 83800

11. WELL TESTS:

Yield gal./min.	Drawdown	Pumping Level	Time
<u>17 Approx</u>	<u>145'</u>	<u>165</u>	<u>2hr</u>

3. LOCATION OF WELL by legal description:

Sketch map location must agree with written location.

Twp. 56 North  or South   
Rge. 1 East  or West   
Sec. 4 1/4 SE 1/4 SE 1/4  
Gov't Lot \_\_\_\_\_ County Bonner  
Lat: \_\_\_\_\_ Long: \_\_\_\_\_

Address of Well Site Same  
Timber Haven off Bottle Bay Rd  
City \_\_\_\_\_

Lt. \_\_\_\_\_ Blk. \_\_\_\_\_ Sub. \_\_\_\_\_ Name \_\_\_\_\_

4. USE:

Domestic  Municipal  Monitor  Irrigation  
 Thermal  Injection  Other \_\_\_\_\_

5. TYPE OF WORK check all that apply (Replacement etc.)

New Well  Modify  Abandonment  Other \_\_\_\_\_

6. DRILL METHOD

Air Rotary  Cable  Mud Rotary  Other \_\_\_\_\_

7. SEALING PROCEDURES

SEAL/FILTER PACK			AMOUNT	METHOD
Material	From	To	Sacks or Pounds	
<u>Bentonite</u>	<u>0</u>	<u>25</u>	<u>8</u>	<u>Overbore</u>

Was drive shoe used?  Y  N Shoe Depth(s) 165

Was drive shoe seal tested?  Y  N How? \_\_\_\_\_

8. CASING/LINER:

Diameter	From	To	Gauge	Material	Casing	Liner	Welded	Threaded
<u>6</u>	<u>+1</u>	<u>165</u>	<u>250</u>	<u>Steel</u>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Length of Headpipe \_\_\_\_\_ Length of Tailpipe \_\_\_\_\_

9. PERFORATIONS/SCREENS

Perforations \_\_\_\_\_ Method \_\_\_\_\_  
Screens \_\_\_\_\_ Screen Type \_\_\_\_\_

From	To	Slot Size	Number	Diameter	Material	Casing	Liner
						<input type="checkbox"/>	<input type="checkbox"/>

10. STATIC WATER LEVEL OR ARTESIAN PRESSURE:  
20' ft. below ground Artesian pressure \_\_\_\_\_ lb.  
Depth flow encountered 163 ft. Describe access port or control devices: well seal

56N 1W 4

12. LITHOLOGIC LOG: (Describe repairs or abandonment) Water

Bore Dia.	From	To	Remarks: Lithology, Water Quality & Temperature	Y	N
<u>8</u>	<u>0</u>	<u>1</u>	<u>Top soil</u>		<input checked="" type="checkbox"/>
<u>8</u>	<u>1</u>	<u>120</u>	<u>Clay Gravel Boulders</u>		<input checked="" type="checkbox"/>
<u>8</u>	<u>120</u>	<u>160</u>	<u>Blue clay Boulders</u>		<input checked="" type="checkbox"/>
<u>8</u>	<u>160</u>	<u>165</u>	<u>Shale Rock</u>		<input checked="" type="checkbox"/>

Completed \_\_\_\_\_ Depth 165 (Measurable)  
Date: Started 2-22-01 Completed 2-28-01

13. DRILLER'S CERTIFICATION

I/We certify that all minimum well construction standards were complied with at the time the rig was removed.

Company Name Bob Pitts & Sons Inc Firm No. 235

Firm Official Bob Pitts Date 2-28-01

and Driller or Operator Mark W. Pitts Date 2-28-01

(Sign once if Firm Official & Operator)